

FEATURES



- 2 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Electric or Gas configurable
- Separate B & O terminals
- Separate heating and cooling swing (cycle rate) adjustments
- Room temperature calibration adjustment
- 5 minute compressor delay protection (selectable on or off)
- Easy wire color coded terminal blocks
- Universal sub-base
- Mounts on wall or junction box
- 24v power
- 5 year limited warranty

SPECIFICATIONS

Display range of temperature.....	41°F to 95°F (5°C to 35°C)
Control range of temperature	44°F to 90°F (7°C to 32°C)
Load rating.....	1 amp per terminal, 1.5 amp max all terminals combined
Display accuracy.....	+/- 1°F
Swing (cycle rate or differential)	Heating is adjustable from 0.2°F to 2.0°F Cooling is adjustable from 0.2°F to 2.0°F
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating ambient.....	32°F to 105°F (0° to 41°C)
Operating humidity	90% non-condensing maximum
Dimensions of thermostat	4.7"W x 4.4"H x 1.1"D
Frequency	916 MHz

The Perfect Fit! The Perfect Choice!

For more information

Call 1-866-233-4022

Email info@perfectcomfort.ca

www.perfectcomfort.ca

We are your best source for reliable products and superior customer service.